

# **Davidsons Fixative, Special**

### 1. Identification

Product Name: Davidsons Fixative, Special

Synonyms: N/A

Recommended Use: Tissue Fixation

Manufacturer: BBC Biochemical 409 Eleanor Lane, Mount Vernon, WA 98273 1-800-635-4477 Item #: 0231ALLE01-GR, 0231GR, 0238ALLE01-GR,

0262ALLE01-GR, 0262GR Web SDS:

Restrictions on Use: Not a beverage.

In Case of Emergency: Chemtrec US 1-800-424-9300 Chemtrec International 703-527-3887

### 2. Hazards Identification

## **OSHA Hazard Classification(s):**

Skin Corrosion - Category 1A Eye Damage - Category 1

Sensitization - Respiratory - Category 1A Sensitization - Skin - Category 1A Germ Cell Mutagenicity - Category 1B

Carcinogenicity - Category 1B

Specific Target Organ Toxicity (single exposure) - Category 1 Specific Target Organ Toxicity (repeated exposure) - Category 2

Flammable Liquids - Category 3

Signal Word: Danger

**Hazard Statement(s):** Causes severe skin burns and eye damage. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. Causes damage to organs(respiratory system). May cause damage to organs (respiratory system, central nervous system, liver, blood) through prolonged or repeated exposure. Flammable liquid and vapor.

### Pictogram(s):









**Precautionary Statement(s):** Prevention: Do not breathe dusts or mists. Wash body thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection. Wear eye protection, face protection. Avoid breathing dust, vapors. Wear NIOSH approved respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, vapors. Do not eat, drink or smoke when using this product. Keep away from heat sources and open flame. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off all contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a doctor. Specific treatment (see first aid section on this label). If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a doctor. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. If exposed or concerned: Get medical attention. If exposed or concerned: Call a doctor. Call a doctor if you feel unwell. In case of fire: Use water, dry chemical, CO2 or foam to extinguish.

Storage: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulations.

Descriptions of Hazards not otherwise classified: N/A Percent of mixture with unknown acute toxicity: N/A

800.635.4477



# **Davidsons Fixative, Special**

## 3. Composition and Information on Ingredients

Chemical Name	Common Name	CAS#	Concentration %
Ethyl Alcohol		64-17-5	Trade Secret
Formaldehyde		50-00-0	Trade Secret
Glacial Acetic Acid		64-19-7	Trade Secret
Water		7732-18-5	Trade Secret
Select Buffers		Trade Secret	Trade Secret

#### 4. First Aid Measures

**Eye Contact:** Wash the eyes immediately with large amounts of water occasionally lifting lower and upper lids, until no evidence of chemical remains (at least 15 to 20 minutes). Immediately remove contact lenses if you are able to do so and it is safe. In case of burns, apply sterile bandages loosely without medication. Get medical attention immediately. If you have experienced appreciable eye irritation from a splash or excessive exposure, you should be referred promptly to an opthamologist for evaluation.

**Skin Contact:** Remove contaminated clothing (including shoes) immediately. Wash the affected area of your body with large amounts of water until no evidence of the chemical remains (at least 15 to 20 minutes). If there are chemical burns, get first aid to cover the area with sterile, dry dressing, and bandages. Get medical attention if you experience appreciable eye or respiratory irritation.

**Inhalation:** Remove the victim from the exposure area to fresh air immediately. Where the formaldehyde concentration may be very high, each rescuer must put on a self-contained breathing apparatus before attempting to remove the victim, and medical personnel should be informed of the formaldehyde exposure immediately. If breathing has stopped, give artificial respiration. Keep the affected person warm and at rest. Qualified first-aid or medical personnel should administer oxygen, if available, and maintain the patient's airways and blood pressure until the victim can be transported to a medical facility. If exposure results in a highly irritated upper respiratory tract and coughing continues for more than 10 minutes, the worker should be hospitalized for observation and treatment.

**Ingestion:** If the victim is conscious, dilute, inactivate, or absorb the ingested formaldehyde by giving milk, activated charcoal, or water. Any organic material will inactivate formaldehyde. Keep affected person warm and at rest. Get medical attention immediately. If vomiting occurs, keep head lower than hips.

Symptoms: Irritation eyes, nose, throat; headache, dizziness. See section 11.

Recommendations for immediate medical care/special treatment: Get medical advice/attention if you feel unwell.

### 5. Fire- Fighting Measures

**Extinguishing Media:** Dry chemical, carbon dioxide, alcohol foam, water. Use water spray to cool fire-exposed containers and disperse vapors.

Fire Hazards (Chemical): OSHA classified Flammable Liquid

Special Protective Equipment: Fire fighters should use self-contained breathing apparatus and protective clothing.

**Precautions for Firefighters:** Carbon monoxide and unidentified organic compounds may be formed during combustion. Vapors can travel distances to ignition source and flash back. Cool fire exposed containers with water. Fine mist or spray may be flammable at temperatures below the flash point. When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive.

#### 6. Accidental Release Measures

**Emergency Procedures:** Evacuate the area of all unnecessary personnel. Wear suitable protective equipment. Eliminate all sources of ignition and provide ventilation.

Protective Equipment: See section 8

Environmental Precautions: Prevent release to the environment by using barriers.

Containment and Clean-Up Procedures: Use barriers to prevent spreading. Collect spill in container. Call waste authorities.

### 7. Handling and Storage

**Handling:** Do not breathe vapors. Do not eat, drink or smoke when using this product. Keep away from heat, sparks, open flames, hot surfaces. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

**Storage:** Store locked up. Store in a cool, well-ventilated place. Keep cool. Store away from heat, sources of ignition and open flame. Keep container tightly sealed when not in use.

800.635.4477



# **Davidsons Fixative, Special**

### 8. Exposure Controls/Personal Protection

### **OSHA Permissible Exposure Limits (PELs):**

Reagent	CAS#	OSHA PEL TWA
Ethyl Alcohol	64-17-5	1000ppm
Formaldehyde	50-00-0	0.75ppm
Glacial Acetic Acid	64-19-7	10ppm

### **ACGIH Threshold Limit Values (TLVs):**

Reagent	CAS#	ACGIH PEL TLV	ACGIH STEL
Ethyl Alcohol	64-17-5		1000ppm
Formaldehyde	50-00-0	0.3 ppm (0.37 mg/m3) Ceiling	
Glacial Acetic Acid	64-19-7	10ppm	15ppm

**Engineering Controls:** Use in a well ventilated area to prevent exposure. Maintain eyewash fountain and quick-drench facilities in work areas.

**Personal Protective Measures:** Wear gloves, lab coat, eye protection and impervious footwear. Contact lenses should not be worn when working with this material.

**Special PPE Requirements:** If ventilation hood not available wear respirator.

### 9. Physical and Chemical Properties Section

Appearance: Green, Liquid Molecular Weight: N/A Molecular Formula: N/A

pH: N/A

**Boiling Point and Boiling Range:** N/A **Melting Point/Freezing Point:** N/A

Flash Point: Approx 29°C

Specific Gravity/Relative Density: N/A

Odor: Vinous, Vinegar like Odor Threshold: N/A

Color: Green

Flammability (solid/gas): N/A

Vapor Density: N/A

Upper/Lower flammability or explosive limits: N/A

Vapor Pressure: N/A Evaporation Rate: N/A

Partition Coefficient: n-octanol/water: N/A

Viscosity: N/A

Auto-ignition temperature: N/A Solubility: Miscible with water.

Decomposition Temperature: N/A

## 10. Stability and Reactivity

Reactivity:

Chemical Stability: Stable

Conditions of Stability/Instability: Stable under normal conditions of temperature and pressure.

800.635.4477



# **Davidsons Fixative, Special**

Stabilizers needed: None

Safety issue indicated by appearance change: N/A

Other: N/A

Hazardous Reactions: N/A

Hazardous Polymerization: Does not occur

Conditions to avoid: Exposure to heat, open flame and sources of ignition.
Classes of Incompatible Materials: Oxidizers, Strong Acids, Strong Bases

Hazardous Decomposition Products: Thermal-oxidation degradation can produce oxides of carbon. Toxic gases and vapors

(I.e. Carbon monoxide) may be released in a fire.

### 11. Toxicological Information

## **Likely Routes of Exposure**

**Eyes:** Solutions splashed in the eye can cause injuries ranging from transient discomfort to severe, permanent corneal clouding and loss of vision. The severity of the effect depends on the concentration of formaldehyde in the solution and whether or not the eyes are flushed with water immediately after the accident.

**Skin:** Formalin is a severe skin irritant and a sensitizer. Contact with formalin causes white discoloration, smarting, drying, cracking, and scaling. Prolonged and repeated contact can cause numbness and a hardening or tanning of the skin. Previously exposed persons may react to future exposure with an allergic eczematous dermatitis or hives.

**Inhalation:** Formaldehyde is highly irritating to the upper respiratory tract and eyes. Concentrations of 0.5 to 2.0 ppm may irritate the eyes, nose, and throat of some individuals.

Ingestion: Ingestion of dilute formaldehyde solutions (0.03-0.04 percent) may cause discomfort in the stomach and pharynx.

Signs or Symptoms of Exposure: Chronic Effects of Exposure Carcinogenicity: Formaldehyde has the potential to cause cancer in humans. Repeated and prolonged exposure increases the risk. Various animal experiments have conclusively shown formaldehyde to be a carcinogen in rats. In humans, formaldehyde exposure has been associated with cancers of the lung, nasopharynx and oropharynx, and nasal passages. Mutagenicity: Formaldehyde is genotoxic in several in vitro test systems showing properties of both an initiator and a promoter. Toxicity: Prolonged or repeated exposure to formaldehyde may result in respiratory impairment. Rats exposed to formaldehyde at 2 ppm developed benign nasal tumors and changes of the cell structure in the nose as well as inflamed mucous membranes of the nose. Structural changes in the epithelial cells in the human nose have also been observed. Some persons have developed asthma or bronchitis following exposure to formaldehyde, most often as the result of an accidental spill involving a single exposure to a high concentration of formaldehyde. Note.-The perception of formaldehyde by odor and eye irritation becomes less sensitive with time as one adapts to formaldehyde. This can lead to overexposure if a worker is relying on formaldehyde's warning properties to alert him or her to the potential for exposure.

Effects from short term exposure (delayed, immediate, chronic): Irritation to the eyes, nose, throat; headache, dizziness, nausea. May cause cancer, mutagenic and reproductive effects. May effect organs (lungs, nose) after single or repeat exposure.

Acute Toxicity (Numerical Measures): N/A

Carcinogenicity (NTP, IARC, OSHA): Contains Formaldehyde IARC Group 1 Carcinogen associated with nasal sinus cancer, nasopharyngeal cancer, myeloid leukemia.

## 12. Ecological Information

**Ecotoxicity:** Formaldehyde is highly toxic to algae, protozoa and other unicellular organisms and slightly toxic to fish. In the atmosphere the material is rapidly degraded by photolysis and photooxidation. Formaldehyde is mobile in the soil. In water or soil, formaldehyde is biodegraded in a few days. Experiments performed on a variety of fish and shrimp show no bioconcentration of formaldehyde.

Persistence and degradability: Acute Aquatic Effects Data for 100% Glacial Acetic Acid 96 h LC-50 (fathead minnow): > 100mg/L 48 h LC-50 (golden orfe): 410 mg/L 48 h LC-50 (mosquito fish): 251 mg/L 96 h LC-50 (daphnid): > 100 mg/L

**Bioaccumulation Potential (octanol-water partition coefficient, BCF):** Oxygen Demand Data for 100% Glacial Acetic Acid BOD-5: 340-880 mg/g BOD-20: 900 mg/g COD: 1,030 mg/g

Mobility in the soil:

Adverse Environmental Effects: This material may cause adverse environmental effects.

### 13. Disposal Considerations

800.635.4477

www.bbcus.com



# **Davidsons Fixative, Special**

Recommended Disposal Containers: Check with your local waste authorities\*

Recommended Disposal Methods: Do not dispose of in drains, check with your local waste authorities.\*

Physical/Chemical Properties affecting Disposal: See section 2 and section 9 applicable information.\*

Special Precautions for Landfill and Incineration Activities: Check with your local waste authorities.\*

Waste Stream: Consult your local or regional authorities.\*

### **14. Transport Information**

**UN Number:** UN1170

**UN Proper Shipping Name:** Ethanol Solutions

Transport Hazard Class(es): 3
Packing Group Number: III

**Environmental Hazards (IMDG code):** 

Marine Pollutant: No

Transport in Bulk (IBC Code): N/A Special Transport Precautions: N/A

### 15. Regulatory Information

OSHA: DOT: EPA: CPSC:



# **Davidsons Fixative, Special**


### 16. Other Information

Revision Date: 08/29/2014

#### **NFPA**

Health	2
Fire Hazard	3
Reactivity	1
Specific Hazard	

National Fire Protection Association (USA) NFPA



### **HMIS**

Health	2
Flammability	3
Physical Hazard	1
Personal Protection	

#### Hazardous Material Information System HMIS



#### Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.