

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Formalin, Neutral Buffered with 10% Alcohol

Product Code: 10ANB0507P

Intended Use of the Product

Fixative. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

StatLab Medical Products

2090 Commerce Drive

McKinney, TX 75069

800-442-3573

972-436-1369 Fax

www.statlab.com

Emergency Telephone Number

Emergency Number : CHEMTREC 800-424-9300 (USA & Canada)

CHEMTREC 703-527-3887 (International)

Non-transport 972-436-1010 (USA)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flammable Liquid 3 H226

Acute Toxicity (oral) Category 4 H302

Acute toxicity (inhalation: gas) Category 4 H332

Skin Irritation 2 H315

Eye Damage 1 H318

Skin Sensitization 1 H317

Carcinogenicity 2 H351

Specific Target Organ Toxicity (Single Exposure) Category 1 H370

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS02



GHS05



GHS07



GHS08

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H226 - Flammable liquid and vapor.

H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H332 - Harmful if inhaled.

H351 - Suspected of causing cancer.

H370 - Causes damage to organs.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, sparks, open flames, hot surfaces. No smoking.

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors, mist, spray.
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear eye protection, protective clothing, protective gloves.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a POISON CENTER or doctor.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P321 - Specific treatment (see Section 4).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Aquatic Acute 3 H402 - Harmful to aquatic life.

P273 - Avoid release to the environment.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Ethyl alcohol	(CAS No) 64-17-5	7.21	Flammable Liquid 2, H225 Eye Irritation 2A, H319 Aquatic Acute 3, H402
Formaldehyde	(CAS No) 50-00-0	3.83	Acute Toxicity 3 (Oral), H301 Acute Toxicity 3 (Dermal), H311 Acute Toxicity 3 (Inhalation:gas), H331 Skin Corrosion 1B, H314 Eye Damage 1, H318 Skin Sensitization 1, H317 Carcinogenicity 2, H351 Aquatic Acute 2, H401
Methyl alcohol	(CAS No) 67-56-1	1.26	Flammable Liquid 2, H225 Acute Toxicity 3 (Oral), H301 Acute Toxicity 3 (Dermal), H311 Acute Toxicity 3 (Inhalation:vapor), H331 Specific Target Organ Toxicity Single Exposure 1, H370

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Isopropyl alcohol	(CAS No) 67-63-0	0.4	Flammable Liquid 2, H225 Eye Irritation 2A, H319 Specific Target Organ Toxicity Single Exposure 3, H336
-------------------	------------------	-----	--

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Assure fresh air breathing. Call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Immediately flush skin with plenty of water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Harmful if inhaled. Harmful if swallowed. Causes serious eye damage. Causes skin irritation. May cause an allergic reaction in sensitive individuals. Suspected of causing cancer. Causes damage to organs.

Inhalation: High concentration of vapors may induce: headache, dizziness, drowsiness, nausea and vomiting. Harmful if inhaled.

Skin Contact: Causes skin irritation. Exposure may produce an allergic reaction.

Eye Contact: Causes serious eye damage.

Ingestion: Harmful if swallowed.

Chronic Symptoms: May cause cancer. May produce an allergic reaction.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Powder, alcohol-resistant foam, water spray, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts with strong oxidants causing fire and explosion hazard.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist, or gas.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s)

Fixative. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Formaldehyde (50-00-0)		
Mexico	OEL Ceiling (mg/m ³)	3 mg/m ³
Mexico	OEL Ceiling (ppm)	2 ppm
USA ACGIH	ACGIH Ceiling (ppm)	0.3 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)
USA NIOSH	NIOSH REL (TWA) (ppm)	0.016 ppm
USA NIOSH	NIOSH REL (ceiling) (ppm)	0.1 ppm
USA IDLH	US IDLH (ppm)	20 ppm
Alberta	OEL Ceiling (mg/m ³)	1.3 mg/m ³
Alberta	OEL Ceiling (ppm)	1 ppm
Alberta	OEL TWA (mg/m ³)	0.9 mg/m ³
Alberta	OEL TWA (ppm)	0.75 ppm
British Columbia	OEL Ceiling (ppm)	1 ppm
British Columbia	OEL TWA (ppm)	0.3 ppm
Manitoba	OEL Ceiling (ppm)	0.3 ppm
New Brunswick	OEL STEL (ppm)	1.5 ppm
New Brunswick	OEL TWA (ppm)	0.5 ppm
Newfoundland & Labrador	OEL Ceiling (ppm)	0.3 ppm
Nova Scotia	OEL Ceiling (ppm)	0.3 ppm
Nunavut	OEL Ceiling (mg/m ³)	2.4 mg/m ³
Nunavut	OEL Ceiling (ppm)	2 ppm
Northwest Territories	OEL Ceiling (mg/m ³)	2.4 mg/m ³
Northwest Territories	OEL Ceiling (ppm)	2 ppm
Ontario	OEL Ceiling (ppm)	1.5 ppm
Ontario	OEL STEL (ppm)	1.0 ppm
Prince Edward Island	OEL Ceiling (ppm)	0.3 ppm
Québec	PLAFOND (mg/m ³)	3 mg/m ³
Québec	PLAFOND (ppm)	2 ppm
Saskatchewan	OEL Ceiling (ppm)	0.3 ppm

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Yukon	OEL Ceiling (mg/m ³)	3 mg/m ³
Yukon	OEL Ceiling (ppm)	2 ppm
Ethyl alcohol (64-17-5)		
Mexico	OEL TWA (mg/m ³)	1900 mg/m ³
Mexico	OEL TWA (ppm)	1000 ppm
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
Alberta	OEL TWA (mg/m ³)	1880 mg/m ³
Alberta	OEL TWA (ppm)	1000 ppm
British Columbia	OEL STEL (ppm)	1000 ppm
Manitoba	OEL STEL (ppm)	1000 ppm
New Brunswick	OEL TWA (mg/m ³)	1880 mg/m ³
New Brunswick	OEL TWA (ppm)	1000 ppm
Newfoundland & Labrador	OEL STEL (ppm)	1000 ppm
Nova Scotia	OEL STEL (ppm)	1000 ppm
Nunavut	OEL STEL (mg/m ³)	2355 mg/m ³
Nunavut	OEL STEL (ppm)	1250 ppm
Nunavut	OEL TWA (mg/m ³)	1884 mg/m ³
Nunavut	OEL TWA (ppm)	1000 ppm
Northwest Territories	OEL STEL (mg/m ³)	2355 mg/m ³
Northwest Territories	OEL STEL (ppm)	1250 ppm
Northwest Territories	OEL TWA (mg/m ³)	1884 mg/m ³
Northwest Territories	OEL TWA (ppm)	1000 ppm
Ontario	OEL STEL (ppm)	1000 ppm
Prince Edward Island	OEL STEL (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1880 mg/m ³
Québec	VEMP (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm
Yukon	OEL STEL (mg/m ³)	1900 mg/m ³
Yukon	OEL STEL (ppm)	1000 ppm
Yukon	OEL TWA (mg/m ³)	1900 mg/m ³
Yukon	OEL TWA (ppm)	1000 ppm
Isopropyl alcohol (67-63-0)		
Mexico	OEL TWA (mg/m ³)	980 mg/m ³
Mexico	OEL TWA (ppm)	400 ppm
Mexico	OEL STEL (mg/m ³)	1225 mg/m ³
Mexico	OEL STEL (ppm)	500 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Alberta	OEL STEL (mg/m ³)	984 mg/m ³
Alberta	OEL STEL (ppm)	400 ppm
Alberta	OEL TWA (mg/m ³)	492 mg/m ³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	400 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	400 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m ³)	1230 mg/m ³
New Brunswick	OEL STEL (ppm)	500 ppm
New Brunswick	OEL TWA (mg/m ³)	983 mg/m ³
New Brunswick	OEL TWA (ppm)	400 ppm
Newfoundland & Labrador	OEL STEL (ppm)	400 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	400 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m ³)	1228 mg/m ³
Nunavut	OEL STEL (ppm)	500 ppm
Nunavut	OEL TWA (mg/m ³)	983 mg/m ³
Nunavut	OEL TWA (ppm)	400 ppm
Northwest Territories	OEL STEL (mg/m ³)	1228 mg/m ³
Northwest Territories	OEL STEL (ppm)	500 ppm
Northwest Territories	OEL TWA (mg/m ³)	983 mg/m ³
Northwest Territories	OEL TWA (ppm)	400 ppm
Ontario	OEL STEL (ppm)	400 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	400 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m ³)	1230 mg/m ³
Québec	VECD (ppm)	500 ppm
Québec	VEMP (mg/m ³)	985 mg/m ³
Québec	VEMP (ppm)	400 ppm
Saskatchewan	OEL STEL (ppm)	400 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m ³)	1225 mg/m ³
Yukon	OEL STEL (ppm)	500 ppm
Yukon	OEL TWA (mg/m ³)	980 mg/m ³
Yukon	OEL TWA (ppm)	400 ppm
Methyl alcohol (67-56-1)		
Mexico	OEL TWA (mg/m ³)	260 mg/m ³
Mexico	OEL TWA (ppm)	200 ppm
Mexico	OEL STEL (mg/m ³)	310 mg/m ³
Mexico	OEL STEL (ppm)	250 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

USA IDLH	US IDLH (ppm)	6000 ppm
Alberta	OEL STEL (mg/m ³)	328 mg/m ³
Alberta	OEL STEL (ppm)	250 ppm
Alberta	OEL TWA (mg/m ³)	262 mg/m ³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	250 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	250 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m ³)	328 mg/m ³
New Brunswick	OEL STEL (ppm)	250 ppm
New Brunswick	OEL TWA (mg/m ³)	262 mg/m ³
New Brunswick	OEL TWA (ppm)	200 ppm
Newfoundland & Labrador	OEL STEL (ppm)	250 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	250 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m ³)	328 mg/m ³
Nunavut	OEL STEL (ppm)	250 ppm
Nunavut	OEL TWA (mg/m ³)	262 mg/m ³
Nunavut	OEL TWA (ppm)	200 ppm
Northwest Territories	OEL STEL (mg/m ³)	328 mg/m ³
Northwest Territories	OEL STEL (ppm)	250 ppm
Northwest Territories	OEL TWA (mg/m ³)	262 mg/m ³
Northwest Territories	OEL TWA (ppm)	200 ppm
Ontario	OEL STEL (ppm)	250 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	250 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m ³)	328 mg/m ³
Québec	VECD (ppm)	250 ppm
Québec	VEMP (mg/m ³)	262 mg/m ³
Québec	VEMP (ppm)	200 ppm
Saskatchewan	OEL STEL (ppm)	250 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m ³)	310 mg/m ³
Yukon	OEL STEL (ppm)	250 ppm
Yukon	OEL TWA (mg/m ³)	260 mg/m ³
Yukon	OEL TWA (ppm)	200 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective clothing. Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: When effective engineering controls are not feasible, appropriate respirators shall be used. Personal Protective Equipment must be selected by trained personnel, taking into account the type of hazardous materials it should protect from, the nature of the work, the expected exposure, and the facial characteristics of the wearers; proper fit is of paramount importance. Ensure the respiratory protection program meets the requirements of OSHA 29 CFR 1910.134.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, colorless liquid
Odor	: Pungent
Odor Threshold	: Not available
pH	: 6.9 - 7.1
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: 51.49 °C (124.68 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: 1.08 - 1.1 (water = 1)
Solubility	: Soluble in water
Partition Coefficient: N-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not available
Explosion Data – Sensitivity to Static Discharge	: Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts violently with strong oxidants causing fire and explosion hazard.

Chemical Stability: Flammable liquid and vapor.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur. Methyl alcohol is added as an inhibitor of formaldehyde and prevents polymerization.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Ignition sources. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Harmful if inhaled. Harmful if swallowed.

LD50 and LC50 Data:

Formalin, Neutral Buffered with 10% Alcohol	
ATE US (oral)	1964.637 mg/kg body weight
ATE US (gases)	18,276.762 ppmV/4h

Skin Corrosion/Irritation: Causes skin irritation. (pH: 6.9 - 7.1)

Serious Eye Damage/Irritation: Causes serious eye damage. (pH: 6.9 - 7.1)

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Suspected of causing cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Causes damage to organs.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: High concentration of vapors may induce: headache, dizziness, drowsiness, nausea and vomiting. Harmful if inhaled.

Symptoms/Injuries After Skin Contact: Causes skin irritation. Exposure may produce an allergic reaction.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Harmful if swallowed.

Chronic Symptoms: May cause cancer. May produce an allergic reaction.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Formaldehyde (50-00-0)	
LD50 Dermal Rat	1000 mg/kg
ATE US (gases)	700.00 ppmV/4h
Ethyl alcohol (64-17-5)	
LD50 Oral Rat	10470 mg/kg
LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat	124.7 mg/l/4h
Isopropyl alcohol (67-63-0)	
LD50 Oral Rat	4710 mg/kg
LD50 Dermal Rabbit	4059 mg/kg
LC50 Inhalation Rat	72600 mg/m ³ (Exposure time: 4 h)
Methyl alcohol (67-56-1)	
LC50 Inhalation Rat	22500 ppm (Exposure time: 8 h)
ATE US (oral)	100.00 mg/kg body weight
ATE US (dermal)	300.00 mg/kg body weight
ATE US (vapors)	3.00 mg/l/4h

Carcinogenicity

Formaldehyde (50-00-0)	
IARC Group	1
National Toxicity Program (NTP) Status	Known Human Carcinogens.
Isopropyl alcohol (67-63-0)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life.

Ecology - Water: Readily biodegrades. Evaporates to moderate extent. Does not bioaccumulate.

Formaldehyde (50-00-0)	
LC50 Fish 1	22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	1510 µg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Ethyl alcohol (64-17-5)	
LC50 Fish 1	12.0 - 16.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Isopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodemus subspicatus)
LC 50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)
Methyl alcohol (67-56-1)	
LC50 Fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Persistence and Degradability

Formalin, Neutral Buffered with 10% Alcohol	
Persistence and Degradability	The substance is biodegradable. Unlikely to persist.
Ethyl alcohol (64-17-5)	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Formalin, Neutral Buffered with 10% Alcohol	
Bioaccumulative Potential	Not expected to bioaccumulate.
Formaldehyde (50-00-0)	
Log Pow	0.35 (at 25 °C)
Ethyl alcohol (64-17-5)	
Log Pow	-0.32
Bioaccumulative Potential	Not established.
Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)
Methyl alcohol (67-56-1)	
BCF Fish 1	< 10
Log Pow	-0.77

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

This product meets the limited quantity exception for transportation. This product has an inner packaging less than 5.0L (1.3 gallon). Except for transportation by aircraft, this product is excepted from labelling requirements.

14.1. UN Number

UN-No.(DOT) : 1993
DOT NA no. : UN1993

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
(Contains: Ethyl alcohol, Isopropyl alcohol, Formaldehyde)

UN technical shipping descriptor : (Formalin)

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Department of Transportation (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard Classes

Hazard Labels (DOT) : 3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name

Packing Group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional

Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional Information

Emergency Response Guide (ERG) : 128

Number

Transport by Sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

MFAG-No : 171

Air Transport

DOT Quantity Limitations Passenger : 60 L

Aircraft/Rail (49 CFR 173.27)

DOT Quantity Limitations Cargo Aircraft : 220 L

Only (49 CFR 175.75)

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Formalin, Neutral Buffered with 10% Alcohol	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
	Delayed (chronic) health hazard
	Fire hazard

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Formaldehyde (50-00-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard
SARA Section 313 - Emission Reporting	0.1 %

Ethyl alcohol (64-17-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Isopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)

Methyl alcohol (67-56-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard
SARA Section 313 - Emission Reporting	1.0 %

US State Regulations

Formaldehyde (50-00-0)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

Ethyl alcohol (64-17-5)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.

Methyl alcohol (67-56-1)	
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.

Formaldehyde (50-00-0)	
U.S. - California - SCAQMD - Toxic Air Contaminants - Carcinogens	
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute	
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic	
U.S. - California - SDAPCD - Toxic Air Contaminants - Carcinogenic Impacts Must Be Calculated	
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)	
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)	
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities	
U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities	
U.S. - Delaware - Accidental Release Prevention Regulations - Toxic Endpoints	
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities	

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Idaho - Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - Acceptable Maximum Peak Above the Ceiling Concentration for an 8-Hour Shift
U.S. - Idaho - Occupational Exposure Limits - Ceilings
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminant Carcinogens
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TEELs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Michigan - Process Safety Management Highly Hazardous Chemicals
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - New Hampshire - Prohibited Volatile Organic Compounds
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New York - Occupational Exposure Limits - Ceilings
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Priority Chemical Avoidance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Carolina - Control of Toxic Air Pollutants
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Unit Risk Factors
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities
U.S. - Ohio - Extremely Hazardous Substances - Threshold Quantities
U.S. - Oregon - Permissible Exposure Limits - STELs
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Hazardous Waste - Hazardous Constituents
U.S. - Vermont - Permissible Exposure Limits - Ceilings
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Dangerous Waste - Dangerous Waste Constituents List
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - West Virginia - Air Quality - Toxic Air Pollutant Emission Limits
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
U.S. - Wyoming - Process Safety Management - Highly Hazardous Chemicals

Ethyl alcohol (64-17-5)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Effects Screening Levels - Long Term

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELS
U.S. - Washington - Permissible Exposure Limits - TWAs

Isopropyl alcohol (67-63-0)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Connecticut - Volatile Substances
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELS
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELS
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Tennessee - Occupational Exposure Limits - STELS
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - STELS
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELS
U.S. - Washington - Permissible Exposure Limits - TWAs

Methyl alcohol (67-56-1)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Connecticut - Volatile Substances
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - Skin Designations
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New York - Occupational Exposure Limits - Skin Designations
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Vermont - Permissible Exposure Limits - Skin Designations
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - Skin Designations
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Canadian Regulations

Formalin, Neutral Buffered with 10% Alcohol

WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--



Formaldehyde (50-00-0)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 0.1 %

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 0.1 %

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Methyl alcohol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 04/06/2016

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Acute Tox. 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H370	Causes damage to organs
H401	Toxic to aquatic life
H402	Harmful to aquatic life

NFPA Health Hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA Fire Hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA Reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 0 Minimal Hazard

Physical

: 0 Minimal Hazard

Formalin, Neutral Buffered with 10% Alcohol

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Party Responsible for the Preparation of This Document

StatLab Medical Products

Phone Number: 800-442-3573

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2