

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mixture

**Product Name:** Formalin, Neutral Buffered with 17% Alcohol

**Product Code:** 17ANB0507

### Intended Use of the Product

Fixative. For professional use only.

### Name, Address, and Telephone of the Responsible Party

#### **Company**

StatLab Medical Products

2090 Commerce Drive

McKinney, TX 75069

800-442-3573

[www.statlab.com](http://www.statlab.com)

### Emergency Telephone Number

**Emergency Number** : CHEMTREC 800-424-9300 (USA & Canada)

CHEMTREC 703-527-3887 (International)

Non-transport 800-225-8867 (USA)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Flammable Liquid 3 H226

Acute Toxicity 4 (Oral) H302

Acute Toxicity 4 (Inhalation:gas) H332

Eye Irritation 2A H319

Skin Sensitization 1 H317

Carcinogenicity 2 H351

Specific Target Organ Toxicity - Single Exposure 1 H370

Full text of H-phrases: see section 16

### Label Elements

#### **GHS-US Labeling**

#### **Hazard Pictograms (GHS-US)**



#### **Signal Word (GHS-US)**

: **Danger**

#### **Hazard Statements (GHS-US)**

: H226 - **Flammable liquid and vapor.**  
 H302+H332 - **Harmful if swallowed or if inhaled.**  
 H317 - May cause an allergic skin reaction.  
 H319 - **Causes serious eye irritation, skin and respiratory irritation.**  
 H351 - **May cause cancer.**  
 H370 - **Causes damage to organs.**

#### **Precautionary Statements (GHS-US)**

: P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.  
 P233 - Keep container tightly closed.  
 P240 - Ground/bond container and receiving equipment.  
 P241 - Use explosion-proof electrical, lighting, ventilating equipment.  
 P242 - Use only non-sparking tools.

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapors, spray, mist.  
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.  
P302+P352 - If on skin: Wash with plenty of water.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P307+P311 - If exposed: Call a poison center/doctor.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center or doctor if you feel unwell.  
P321 - Specific treatment (see Section 4 on this SDS).  
P330 - Rinse mouth.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### Other Hazards

Aquatic Acute 3

H402 - Harmful to aquatic life.

P273 - Avoid release to the environment.

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Ethyl alcohol	(CAS No) 64-17-5	12.4	Flammable Liquid 2, H225 Eye Irritation 2A, H319 Aquatic Acute 3, H402
Methyl alcohol	(CAS No) 67-56-1	1.5	Flammable Liquid 2, H225 Acute Toxicity 3 (Oral), H301 Acute Toxicity 3 (Dermal), H311 Acute Toxicity 3 (Inhalation:vapour), H331 Specific Target Organ Toxicity - Single Exposure 1, H370
Formaldehyde	(CAS No) 50-00-0	3.6	Acute Toxicity 3 (Oral), H301 Acute Toxicity 3 (Dermal), H311 Acute Toxicity 3 (Inhalation:gas), H331 Skin Corrosion 1B, H314 Eye Damage 1, H318 Skin Sensitization 1, H317 Carcinogenicity 2, H351 Aquatic Acute 2, H401
Isopropyl alcohol	(CAS No) 67-63-0	0.69	Flammable Liquid 2, H225

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

			Eye Irritation 2A, H319 Specific Target Organ Toxicity - Single Exposure 3, H336
--	--	--	---

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Assure fresh air breathing. Call a POISON CENTER or doctor/physician.

**Skin Contact:** Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

#### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Harmful if swallowed. Harmful if inhaled. Causes serious eye irritation. Exposure may produce an allergic reaction.

**Inhalation:** Harmful if inhaled. High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.

**Skin Contact:** E may produce an allergic reaction.

**Eye Contact:** Causes serious eye irritation. Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Ingestion:** Harmful if swallowed. This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death.

**Chronic Symptoms:** Suspected of causing cancer. May produce an allergic reaction.

#### Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

### SECTION 5: FIRE-FIGHTING MEASURES

#### Extinguishing Media

**Suitable Extinguishing Media:** Powder, alcohol-resistant foam, water spray, carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Flammable liquid and vapor.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts with strong oxidants causing fire and explosion hazard.

#### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>).

#### Reference to Other Sections

Refer to section 9 for flammability properties.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces – No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe vapour or mist.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Ventilate area. Eliminate ignition sources.

#### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

#### Environmental Precautions

Prevent entry to sewers and public waters.

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Methods and Material for Containment and Cleaning Up

**For Containment:** Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Contact competent authorities after a spill.

### Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Proper grounding procedures to avoid static electricity should be followed.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

### Specific End Use(s)

Fixative. For professional use only.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Formaldehyde (50-00-0)		
Mexico	OEL Ceiling (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Mexico	OEL Ceiling (ppm)	2 ppm
USA ACGIH	ACGIH Ceiling (ppm)	0.3 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)
USA NIOSH	NIOSH REL (TWA) (ppm)	0.016 ppm
USA NIOSH	NIOSH REL (ceiling) (ppm)	0.1 ppm
USA IDLH	US IDLH (ppm)	20 ppm
Alberta	OEL Ceiling (mg/m <sup>3</sup> )	1.3 mg/m <sup>3</sup>
Alberta	OEL Ceiling (ppm)	1 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	0.9 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	0.75 ppm
British Columbia	OEL Ceiling (ppm)	1 ppm
British Columbia	OEL TWA (ppm)	0.3 ppm
Manitoba	OEL Ceiling (ppm)	0.3 ppm
New Brunswick	OEL STEL (ppm)	1.5 ppm
New Brunswick	OEL TWA (ppm)	0.5 ppm
Newfoundland & Labrador	OEL Ceiling (ppm)	0.3 ppm
Nova Scotia	OEL Ceiling (ppm)	0.3 ppm
Nunavut	OEL Ceiling (mg/m <sup>3</sup> )	2.4 mg/m <sup>3</sup>
Nunavut	OEL Ceiling (ppm)	2 ppm
Northwest Territories	OEL Ceiling (mg/m <sup>3</sup> )	2.4 mg/m <sup>3</sup>
Northwest Territories	OEL Ceiling (ppm)	2 ppm
Ontario	OEL Ceiling (ppm)	1.5 ppm
Ontario	OEL STEL (ppm)	1.0 ppm
Prince Edward Island	OEL Ceiling (ppm)	0.3 ppm
Québec	PLAFOND (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Québec	PLAFOND (ppm)	2 ppm

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Saskatchewan</b>	OEL Ceiling (ppm)	0.3 ppm
<b>Yukon</b>	OEL Ceiling (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
<b>Yukon</b>	OEL Ceiling (ppm)	2 ppm
<b>Ethyl alcohol (64-17-5)</b>		
<b>Mexico</b>	OEL TWA (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
<b>Mexico</b>	OEL TWA (ppm)	1000 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	1000 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	1000 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	1000 ppm
<b>USA IDLH</b>	US IDLH (ppm)	3300 ppm (10% LEL)
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	1880 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	1000 ppm
<b>British Columbia</b>	OEL STEL (ppm)	1000 ppm
<b>Manitoba</b>	OEL STEL (ppm)	1000 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	1880 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	1000 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	1000 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	1000 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	2355 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	1250 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	1884 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	1000 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	2355 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	1250 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	1884 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	1000 ppm
<b>Ontario</b>	OEL STEL (ppm)	1000 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	1000 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	1880 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	1000 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	1250 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	1000 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	1000 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	1000 ppm
<b>Isopropyl alcohol (67-63-0)</b>		
<b>Mexico</b>	OEL TWA (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
<b>Mexico</b>	OEL TWA (ppm)	400 ppm
<b>Mexico</b>	OEL STEL (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
<b>Mexico</b>	OEL STEL (ppm)	500 ppm
<b>USA ACGIH</b>	ACGIH TWA (ppm)	200 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	400 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	400 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	400 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	500 ppm

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>USA IDLH</b>	US IDLH (ppm)	2000 ppm (10% LEL)
<b>Alberta</b>	OEL STEL (mg/m <sup>3</sup> )	984 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL (ppm)	400 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	492 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	200 ppm
<b>British Columbia</b>	OEL STEL (ppm)	400 ppm
<b>British Columbia</b>	OEL TWA (ppm)	200 ppm
<b>Manitoba</b>	OEL STEL (ppm)	400 ppm
<b>Manitoba</b>	OEL TWA (ppm)	200 ppm
<b>New Brunswick</b>	OEL STEL (mg/m <sup>3</sup> )	1230 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL (ppm)	500 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	400 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	400 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	200 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	400 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	200 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	1228 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	500 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	400 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	1228 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	500 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	400 ppm
<b>Ontario</b>	OEL STEL (ppm)	400 ppm
<b>Ontario</b>	OEL TWA (ppm)	200 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	400 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	200 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	1230 mg/m <sup>3</sup>
<b>Québec</b>	VECD (ppm)	500 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	985 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	400 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	400 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	200 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	500 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	400 ppm
<b>Methyl alcohol (67-56-1)</b>		
<b>Mexico</b>	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
<b>Mexico</b>	OEL TWA (ppm)	200 ppm
<b>Mexico</b>	OEL STEL (mg/m <sup>3</sup> )	310 mg/m <sup>3</sup>
<b>Mexico</b>	OEL STEL (ppm)	250 ppm
<b>USA ACGIH</b>	ACGIH TWA (ppm)	200 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	250 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	200 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	200 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup>

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	250 ppm
<b>USA IDLH</b>	US IDLH (ppm)	6000 ppm
<b>Alberta</b>	OEL STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL (ppm)	250 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	200 ppm
<b>British Columbia</b>	OEL STEL (ppm)	250 ppm
<b>British Columbia</b>	OEL TWA (ppm)	200 ppm
<b>Manitoba</b>	OEL STEL (ppm)	250 ppm
<b>Manitoba</b>	OEL TWA (ppm)	200 ppm
<b>New Brunswick</b>	OEL STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL (ppm)	250 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	200 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	250 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	200 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	250 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	200 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	250 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	200 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	250 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	200 ppm
<b>Ontario</b>	OEL STEL (ppm)	250 ppm
<b>Ontario</b>	OEL TWA (ppm)	200 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	250 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	200 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
<b>Québec</b>	VECD (ppm)	250 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	200 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	250 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	200 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	310 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	250 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	200 ppm

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Full protective flameproof clothing. Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** When effective engineering controls are not feasible, appropriate respirators shall be used. Personal Protective Equipment must be selected by trained personnel, taking into account the type of hazardous materials it should protect from, the nature of the work, the expected exposure, and the facial characteristics of the wearers; proper fit is of paramount importance. Ensure the respiratory protection program meets the requirements of OSHA 29 CFR 1910.134.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, colorless liquid
Odor	: Pungent.
Odor Threshold	: Not available
pH	: 6.9 - 7.1
Evaporation Rate	: Not available
Melting/Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: 42.43 °C (108.37 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density / Specific Gravity	: 1.08 - 1.1 (water = 1)
Solubility	: Soluble in water.
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Reacts with strong oxidants causing fire and explosion hazard.

**Chemical Stability:** Flammable liquid and vapor.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur. Methyl alcohol is added as an inhibitor of formaldehyde and prevents polymerization.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Open flame. Ignition sources. Incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity:** Oral: Harmful if swallowed. Inhalation:gas: Harmful if inhaled.

**LD50 and LC50 Data:**

Formalin, Neutral Buffered with 17% Alcohol	
ATE US (oral)	1,960.78 mg/kg body weight
ATE US (gases)	19,444.44 ppmV/4h

**Skin Corrosion/Irritation:** Not classified. (pH: 6.9 - 7.1)

**Serious Eye Damage/Irritation:** Causes serious eye irritation. (pH: 6.9 - 7.1)

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.



# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Suspected of causing cancer.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Causes damage to organs.

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Harmful if inhaled. High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. Exposure may produce an allergic reaction.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation. Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Symptoms/Injuries After Ingestion:** Harmful if swallowed. This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death.

**Chronic Symptoms:** Suspected of causing cancer. May produce an allergic reaction.

### Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

<b>Formaldehyde (50-00-0)</b>	
LD50 Oral Rat	100 mg/kg
LD50 Dermal Rat	270 mg/kg
ATE US (gases)	700.00 ppmV/4h
<b>Ethyl alcohol (64-17-5)</b>	
LD50 Oral Rat	10470 mg/kg
LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat	124.7 mg/l/4h
<b>Isopropyl alcohol (67-63-0)</b>	
LD50 Oral Rat	4710 mg/kg
LD50 Dermal Rabbit	4059 mg/kg
LC50 Inhalation Rat	72600 mg/m <sup>3</sup> (Exposure time: 4 h)
<b>Methyl alcohol (67-56-1)</b>	
LC50 Inhalation Rat	22500 ppm (Exposure time: 8 h)
ATE US (oral)	100.00 mg/kg body weight
ATE US (dermal)	300.00 mg/kg body weight
ATE US (vapors)	3.00 mg/l/4h
<b>Formaldehyde (50-00-0)</b>	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
<b>Isopropyl alcohol (67-63-0)</b>	
IARC Group	3

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

**Ecology - General:** Harmful to aquatic life.

<b>Formaldehyde (50-00-0)</b>	
LC50 Fish 1	22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	1510 µg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>Ethyl alcohol (64-17-5)</b>	
LC50 Fish 1	12.0 - 16.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Isopropyl alcohol (67-63-0)</b>	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC 50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
<b>Methyl alcohol (67-56-1)</b>	
LC50 Fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

### Persistence and Degradability

<b>Formalin, Neutral Buffered with 17% Alcohol</b>	
Persistence and Degradability	The substance is biodegradable. Unlikely to persist.
<b>Ethyl alcohol (64-17-5)</b>	
Persistence and Degradability	Not established.

### Bioaccumulative Potential

<b>Formalin, Neutral Buffered with 17% Alcohol</b>	
Bioaccumulative Potential	Not expected to bioaccumulate.
<b>Formaldehyde (50-00-0)</b>	
Log Pow	0.35 (at 25 °C)
<b>Ethyl alcohol (64-17-5)</b>	
Log Pow	-0.32
Bioaccumulative Potential	Not established.
<b>Isopropyl alcohol (67-63-0)</b>	
Log Pow	0.05 (at 25 °C)
<b>Methyl alcohol (67-56-1)</b>	
BCF Fish 1	< 10
Log Pow	-0.77

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

## SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

**Note:** This product meets a limited quantity exemption. The shipping information below only applies when the product is shipped in quantities greater than 5 L (1.32 Gallons).

### 14.1. UN Number

UN-No.(DOT) : 1993  
DOT NA no. : UN1993

### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.  
(Contains: Ethyl alcohol, Isopropyl alcohol, Methyl alcohol)  
UN technical shipping descriptor : (Formalin)  
Department of Transportation (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard Classes

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Hazard Labels (DOT)** : 3 - Flammable liquid



**DOT Symbols** : G - Identifies PSN requiring a technical name

**Packing Group (DOT)** : III - Minor Danger

**DOT Special Provisions (49 CFR 172.102)** : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

**DOT Packaging Exceptions (49 CFR 173.xxx)** : 150

**DOT Packaging Non Bulk (49 CFR 173.xxx)** : 203

**DOT Packaging Bulk (49 CFR 173.xxx)** : 242

### 14.3. Additional Information

**Emergency Response Guide (ERG) Number** : 128

**Limited Quantity Exception** : Except when transported by aircraft, this product meets the limited quantity exception of 5L.

### Transport by Sea

**DOT Vessel Stowage Location** : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

**MFAG-No** : 171

### Air Transport

**DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27)** : 60 L

**DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75)** : 220 L

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

<b>Formalin, Neutral Buffered with 17% Alcohol</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
<b>Formaldehyde (50-00-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on United States SARA Section 313	

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>SARA Section 302 Threshold Planning Quantity (TPQ)</b>	500
<b>SARA Section 311/312 Hazard Classes</b>	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard
<b>SARA Section 313 - Emission Reporting</b>	0.1 %
<b>Ethyl alcohol (64-17-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Isopropyl alcohol (67-63-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>SARA Section 313 - Emission Reporting</b>	1.0 % (only if manufactured by the strong acid process, no supplier notification)
<b>Methyl alcohol (67-56-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>SARA Section 311/312 Hazard Classes</b>	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard
<b>SARA Section 313 - Emission Reporting</b>	1.0 %

### US State Regulations

<b>Formaldehyde (50-00-0)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Ethyl alcohol (64-17-5)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>Methyl alcohol (67-56-1)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.

<b>Formaldehyde (50-00-0)</b>	
U.S. - California - SCAQMD - Toxic Air Contaminants - Carcinogens U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic U.S. - California - SDAPCD - Toxic Air Contaminants - Carcinogenic Impacts Must Be Calculated U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728) U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities U.S. - Delaware - Accidental Release Prevention Regulations - Toxic Endpoints U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Idaho - Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - Acceptable Maximum Peak Above the Ceiling Concentration for an 8-Hour Shift U.S. - Idaho - Occupational Exposure Limits - Ceilings U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Illinois - Toxic Air Contaminant Carcinogens U.S. - Illinois - Toxic Air Contaminants	

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Louisiana - Reportable Quantity List for Pollutants  
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants  
U.S. - Maine - Chemicals of High Concern  
U.S. - Massachusetts - Allowable Ambient Limits (AALs)  
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Threshold Effects Exposure Limits (TEELs)  
U.S. - Massachusetts - Toxics Use Reduction Act  
U.S. - Michigan - Occupational Exposure Limits - STELs  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Michigan - Polluting Materials List  
U.S. - Michigan - Process Safety Management Highly Hazardous Chemicals  
U.S. - Minnesota - Chemicals of High Concern  
U.S. - Minnesota - Groundwater Health Risk Limits  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Hampshire - Prohibited Volatile Organic Compounds  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
U.S. - New Jersey - Environmental Hazardous Substances List  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)  
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria  
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)  
U.S. - New York - Occupational Exposure Limits - Ceilings  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - New York - Priority Chemical Avoidance List  
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances  
U.S. - North Carolina - Control of Toxic Air Pollutants  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
U.S. - North Dakota - Air Pollutants - Unit Risk Factors  
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues  
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities  
U.S. - Ohio - Extremely Hazardous Substances - Threshold Quantities  
U.S. - Oregon - Permissible Exposure Limits - STELs  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups  
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual  
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations  
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories  
U.S. - Tennessee - Occupational Exposure Limits - STELs  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - Effects Screening Levels - Long Term

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Hazardous Waste - Hazardous Constituents  
U.S. - Vermont - Permissible Exposure Limits - Ceilings  
U.S. - Vermont - Permissible Exposure Limits - STELs  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Dangerous Waste - Dangerous Waste Constituents List  
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs  
U.S. - West Virginia - Air Quality - Toxic Air Pollutant Emission Limits  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet  
U.S. - Wyoming - Process Safety Management - Highly Hazardous Chemicals

### Ethyl alcohol (64-17-5)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Maine - Chemicals of High Concern  
U.S. - Massachusetts - Allowable Ambient Limits (AALs)  
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Threshold Effects Exposure Limits (TEELs)  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Minnesota - Chemicals of High Concern  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs

### Isopropyl alcohol (67-63-0)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute  
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Connecticut - Volatile Substances  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Toxics Use Reduction Act  
U.S. - Michigan - Occupational Exposure Limits - STELs  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - STELs  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
U.S. - New Jersey - Environmental Hazardous Substances List  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour  
U.S. - Tennessee - Occupational Exposure Limits - STELs  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - STELs  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs

### **Methyl alcohol (67-56-1)**

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)  
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute  
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic  
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)  
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Connecticut - Volatile Substances  
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Illinois - Toxic Air Contaminants  
U.S. - Louisiana - Reportable Quantity List for Pollutants  
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants  
U.S. - Maine - Chemicals of High Concern

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Massachusetts - Allowable Ambient Limits (AALs)  
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Threshold Effects Exposure Limits (TEELs)  
U.S. - Massachusetts - Toxics Use Reduction Act  
U.S. - Michigan - Occupational Exposure Limits - Skin Designations  
U.S. - Michigan - Occupational Exposure Limits - STELs  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Michigan - Polluting Materials List  
U.S. - Minnesota - Chemicals of High Concern  
U.S. - Minnesota - Groundwater Health Risk Limits  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations  
U.S. - Minnesota - Permissible Exposure Limits - STELs  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
U.S. - New Jersey - Environmental Hazardous Substances List  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria  
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)  
U.S. - New York - Occupational Exposure Limits - Skin Designations  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups  
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual  
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations  
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories  
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations  
U.S. - Tennessee - Occupational Exposure Limits - STELs  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - Skin Designations  
U.S. - Vermont - Permissible Exposure Limits - STELs  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List  
U.S. - Washington - Permissible Exposure Limits - Skin Designations  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs



# Formalin, Neutral Buffered with 17% Alcohol


## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Canadian Regulations

#### Formalin, Neutral Buffered with 17% Alcohol

WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--



#### Formaldehyde (50-00-0)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 0.1 %

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

#### Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 0.1 %

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

#### Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

#### Methyl alcohol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 04/16/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### GHS Full Text Phrases:

Acute Toxicity 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Toxicity 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Toxicity 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Toxicity 3 (Oral)	Acute toxicity (oral) Category 3
Acute Toxicity 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4

# Formalin, Neutral Buffered with 17% Alcohol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Acute Toxicity 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Carcinogenicity 2	Carcinogenicity Category 2
Eye Damage 1	Serious eye damage/eye irritation Category 1
Eye Irritation 2A	Serious eye damage/eye irritation Category 2A
Flammable Liquid 2	Flammable liquids Category 2
Flammable Liquid 3	Flammable liquids Category 3
Skin Corrosion 1B	Skin corrosion/irritation Category 1B
Skin Sensitization 1	Skin sensitization Category 1
Specific Target Organ Toxicity - Single Exposure 1	Specific target organ toxicity (single exposure) Category 1
Specific Target Organ Toxicity - Single Exposure 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H370	Causes damage to organs
H401	Toxic to aquatic life
H402	Harmful to aquatic life

### NFPA Health Hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

### NFPA Fire Hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

### NFPA Reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

#### Health

: 2 Moderate Hazard - Temporary or minor injury may occur

#### Flammability

: 2 Moderate Hazard

#### Physical

: 0 Minimal Hazard

### Party Responsible for the Preparation of This Document

StatLab Medical Products

Phone Number: 800-442-3573

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS